

ITW Permatex Canada
 35 Brownridge Road, Unit 1
 Halton Hills, ON Canada L7G 0C6
 Telephone: (800) 924-6994
 Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC 101BR SENSOR SAFE ULTRA COPPER GASKET MAKER 80 ML
 Item No: 59703
 Product Type: Silicone

II. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | LD50/oral/rat | LC50/inhalation/rat | ACGIH; TLV-TWA |
|--|---------|---------------|---------------------|---------------------|
| POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8 | 50-70 | >40,000 mg/kg | >535 mg/l | |
| POLYDIMETHYLSILOXANE 63148-62-9 | 20-40 | >17 g/kg | not available | |
| MODIFIED SILICON DIOXIDE 68611-44-9 | <10 | not available | not available | |
| VINYL OXIMINOSILANE 2224-33-1 | <7 | not available | not available | |
| IRON OXIDE 1309-37-1 | <3 | >10000 mg/kg | not available | 5 mg/m ³ |
| SILICA, MICA 12001-26-2 | <3 | not available | not available | 3 mg/m ³ |
| 2-BUTANONE OXIME 96-29-7 | 0.5-2.0 | 930 mg/kg | 20 mg/L/4H | |

III. PHYSICAL DATA

Physical State/Appearance: Copper-colored paste
 Odour & Odour Threshold: Mild odour
 Specific Gravity: 1.05
 Evaporation Rate: Not determined
 Vapour Pressure: <5 mmHg @ 21°C
 Vapour Density: Approximately 3
 Freezing Point: Not determined
 pH: 7-8
 Octanol/Water Coefficient: Not determined
 Boiling Point: Not applicable, Polymeric

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
 Hazardous Combustion Products: Formaldehyde, silica fume, oxides of carbon, Oxides of nitrogen, methyl ethyl ketone, possibly methyl ethyl ketoxime.
 Sensitivity to Static Discharge: Sensitivity to static discharge is not expected.
 Conditions of Flammability: None anticipated.
 Flash Point/Range: >95°C COC
 Autoignition Temperature: Not determined
 Upper Explosive Limit: Iron Oxide: 12.5%
 Lower Explosive Limit: Iron Oxide: 2.6%

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
 Materials to avoid: Polymerization can occur, Strong oxidizing agents, Water, Acids
 Conditions of Reactivity: None.
 Hazardous Decomposition Products: Carbon oxides, Oxides of nitrogen, Silicon oxides, Methyl ethyl ketoxime, Formaldehyde

VI. HAZARDS IDENTIFICATION

| | |
|--|--|
| Primary Routes of Exposure: | Eye and skin contact, ingestion, inhalation |
| Existing Conditions Aggravated by Exposure: | Preexisting eye, skin and respiratory disorders |
| Toxicity Information: | (See Effects of Acute Exposure to Product) |
| Effects of Acute Exposure: | Moderately toxic if swallowed. Irritating to mouth, throat and stomach with nausea. |
| Effects of Chronic Exposure: | See (Effects of Acute Exposure to Product). Note: This product does not contain microcrystalline silica. |
| Irritancy of Product: | 2-Butanone oxime vapors produced during cure are toxic and irritate eyes, nose and throat. |
| Sensitization to Product: | (See Effects of Acute Exposure to Product) |
| Carcinogenicity: | (See Effects of Chronic Exposure to Product) |
| Reproductive Toxicity: | (See Effects of Chronic Exposure to Product) |
| Teratogenicity: | (See Effects of Chronic Exposure to Product) |
| Mutagenicity: | (See Effects of Chronic Exposure to Product) |
| Toxicologically Synergistic Products: | None known |
| WHMIS Hazard Class: | D2B TOXIC MATERIALS |

VII. PREVENTATIVE MEASURES

| | |
|---|---|
| Personal Protection | |
| Eyes: | Safety glasses. |
| Skin: | Neoprene or nitrile gloves recommended. |
| Ventilation: | General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator |
| Engineering Controls: | |
| Spill Procedures: | Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery. |
| Protection of Man and Environment: | Follow Canadian and local regulations for disposal. |
| Handling Procedures and Equipment: | Store in a dry area below 35°C. Keep container closed when not in use. |
| Special Handling Information: | Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. Do not wear contact lenses. |
| Comments: | When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde |

VIII. FIRST AID MEASURES

| | |
|----------------------|---|
| Ingestion: | Rinse mouth. Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person. |
| Inhalation: | Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention. |
| Skin Contact: | Wipe off material with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician. |
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists. |

IX. SHIPPING INFORMATION**Canadian Transportation of Dangerous Goods**

| | |
|------------------------------|---------------|
| Proper Shipping Name: | Not regulated |
| Hazard Class: | None |
| UN/ID No: | None |

IATA (Air)

| | |
|------------------------------|---------------|
| Proper Shipping Name: | Not regulated |
| Class or Division: | None |
| UN/ID Number: | None |

IMDG (Vessel)

| | |
|------------------------------|---------------|
| Proper Shipping Name: | Not regulated |
| Hazard Class: | None |
| UN Number: | None |

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0
(HMIS is a registered trademark of the National Paint and Coatings Association)

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0
(NFPA is a registered trademark of the National Fire Protection Association)

X. PREPARATION INFORMATION

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Company: ITW Permatex Canada. 35 Brownridge Rd. Unit 1, Halton Hills, ON L76 0C6

Revision Date: January 21, 2015

Telephone No.: 1-800-924-6994

Revision Number: 5