

RS20LBC Red Stallion Brake Cleaner



Section 1: Chemical Product and Company Identification

Manufacturer / Supplier:

Shrader Canada Limited

Address:

830 Progress Court, Oakville, Ontario L6L 6K1

Revision Date:

06/15/2011

Product Use: Chemical Family: Cleaner Mixture

Section 2: Composition/Information on Ingredients

Component Name:	%	LD50 and LC50	ACGIH TWA	Ecotoxicity - Aquatic Toxicity
Heptane 142-82-5	60-100	Inhalation LC50 Rat:103 g/m³ 4h	= 400 ppm TWA =500 ppm STEL	LC50 (96 h) cichlid fish: 375.0 mg/L. Cond: LC50 (24 h) goldfish: 4.0 mg/L. Cond: LC50 (24 h) mosquito fish: 4900 mg/L. Cond:
Isopropanol 67-63-0	1-5	Dermal LD50 Rabbit:12800 mg/kg Dermal LD50 Rat:12800 mg/kg Oral LD50 Rat:4396 mg/kg Inhalation LC50 Rat:72.6 mg/L 4h	= 200 ppm TWA =400 ppm STEL	LC50 (96 h) fathead minnow (31 days old): 61200 mg/L. Cond: flow-through LC50 (96 h) fathead minnow (29 days old): 94900 mg/L. Cond: flow-through EC50 (5 min) Photobacterium phosphoreum: 35390 mg/L

Section 3: Hazards Identification

Inquestion:

Ingestion of small amounts during normal handling are not likely to cause injury. Larger amounts may cause effects similar to those described under inhalation. Ingestion of large amounts may cause

stomach irritation. Symptoms include nausea, vomiting and diarrhea. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be

fatal.

Inhalation:

High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and

headache to unconsciousness.

Skin Contact:

Skin irritant.

Eye Contact: Chronic Effects: May irritate eyes. Symptoms will include pain, redness and tearing. Reports have associated repeated and prolonged occupational overexposure to various organic solvents with internal organ,

brain and nervous system damage.

Section 4: First Aid Measures

Ingestion: Do not induce vomiting. Never give anything by mouth if victim

is rapidly losing consciousness, is unconscious or is convulsing. Drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Obtain medical

attention immediately.

Inhalation: If inhaled, remove to fresh air. If breathing is difficult give

oxygen. If not breathing give artificial respiration and get

medical attention immediately.

Skin Contact: Remove contaminated clothing and launder before reuse. Wash with

soap and water. Seek medical attention if irritation persists. Immediately flush eyes with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses

if any after the initial flushing and then continue flushing.

Section 5: Fire Fighting Measures

Flash Point (°C):

-8 °C

Flame Projection:

Eye Contact:

Not Applicable.

NFPA Classification:

Flammable Liquid, Class IB

Lower Explosive Limit: 2.0 % Upper Explosive Limit: 12.7 % Autoignition Temp. (°C): 399

Sensitivity to Mechanical Impact:

Not Available

Conditions of Flammability:

Flammable when heated to temperatures above the flash point and on contact with an ignition source. Vapours are heavier than air and may travel or be moved along the ground to an ignition source at locations distant from material handling.

Sensitivity to Static Discharge:

Take precautionary measures against static discharges, such as bonding and grounding when dispensing.

Hazardous Combustion:

Carbon dioxide, carbon monoxide and other unidentified organic compounds.

Extinguishing Media:

Alcohol foam or water fog for large fires. Carbon dioxide or dry chemical for small fires. Use water spray to cool fire exposed containers and prevent bursting. Do not use a direct stream of water.

Section 6: Accidental Release Measures

Leak or Spill Procedures:

Wear suitable protective clothing. Follow applicable explosion and fire precautions during the response. Stop the spill at the source when safe to do so. For large spills, dike the area to prevent spreading. Pump excess to a salvage container. Absorb residues and small spills with a non-flammable absorbent material and collect adsorbate for disposal. For large quantities refer to the environmental ministry.

Section 7: Handling and Storage

Handling Procedures:

Flammable. Keep away from heat, spark, flame and other sources of ignition. Containers of this material may contain hazardous residues when emptied. Do not cut, weld, drill or grind on or near this container. Use good personal hygiene. Avoid smoking, eating and drinking during use. Wash with soap and water after handling.

Storage Requirements:

Flammable. Store in a cool area, away from all sources of heat, ignition and incompatibles. Keep containers tightly closed when not in use. Keep away from children.

Section 8: Exposure Controls / Personal Protection

Respiratory:

Not normally required. If the TLV is exceeded, a NIOSH-approved

respirator is advised.

Gloves:

Nitrile gloves. Eyewear:

Safety glasses. Contact lenses should not be worn. They may

contribute to the severity of the injury.

Clothing: Sufficient clothing to prevent skin contact.

Ventilation: Sufficient mechanical ventilation to maintain exposures below the

TLV. General mechanical ventilation is not recommended as the sole means of controlling exposure. Make-up air should always be

supplied to balance air exhausted.

Other protective equipment: Emergency showers and eyewash facilities should be nearby. The

selection of personal protective equipment will vary depending on

the conditions of use.

Section 9: Physical and Chemical Properties

Physical State:

Liquid

Color:

Not Available

Odour:

Vanilla.

Vapour Density (Air=1):

> 1

VOC %:

100

pH: Solubility in Water: Not Applicable

Specific Gravity (H2O=1):

Negligible

0.70

Viscosity:

< 14cSt @ 40°C 40°C

Section 10: Stability and Reactivity

Conditions of Instability:

Stable at ambient and moderately elevated temperatures and pressures.

Hazardous Polymerization:

Hazardous polymerization will not occur.

Hazardous Decomposition:

See hazardous combustion products.

Incompatible Materials:

Avoid strong oxiding and reducing agents. Avoid strong acids. Avoid strong alkalis.

Conditions of Reactivity:

Avoid excessive heat, sparks and open flame. Avoid contact with incompatible materials.

Section 11: Toxicological Information

Irritancy of Product:

Moderately irritating to eyes and skin.

Sensitization to product:

Contains no known skin or respiratory sensitizers.

Carcinogenicity:

No components are listed as carcinogens by ACGIH, IARC, OSHA, or NTP.

Reproductive Effects:

Not Available

Teratogenicity:

Not Available

Mutagenicity: Not Available

Synergystic Products:

Not Available

Section 12: Ecological Information

Environmental:

May be harmful to aquatic life. See composition/information on

ingredients.

Biodegradability:

Not available.

Section 13: Disposal Considerations

Waste Disposal:

Reuse or recycling should be given priority over disposal under any circumstances. Do not dump unused contents into sewers, on the ground or into any body of water. Destroy by incineration or biological treatment according to applicable legislation. Dispose

of in accordance with municipal, provincial and federal

regulations.

Section 14: Transportation Information

Road shipment:

FLAMMABLE LIQUID, N.O.S. (Heptane, Isopropanol), Class 3, UN1993,

PG II, ERG #128.

Marine shipment:

UN1993, FLAMMABLE LIQUID, N.O.S. (Heptane, Isopropanol), Class 3,

PG II, EmS# F-E, S-E

Air Shipment:

Flammable liquid, N.O.S. (Heptane, Isopropanol), Class 3, UN1993,

PG II, PI 305/307.

Exemption:

Product is prohibited for shipment as a consumer commodity.

Section 15: Regulatory Information

WHMIS: B2 D2B

CEPA: All components are listed on the Domestic Substances List (DSL).

CPR Compliance: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

Section 16: Other Information

HMIS Rating:

130B

Prepared By:

Regulatory Compliance, Shrader Canada Limited

Information Tel #:

800-201-9486, 905-847-0222

Information Fax #:

905-847-5404

CANUTEC EMERGENCY: 613-996-6666