

**SHRADER CANADA** **RS1LDFC  
Red Stallion Diesel Fuel Conditioner****Section 1: Chemical Product and Company Identification**

**Manufacturer / Supplier:** Shrader Canada Limited  
**Address:** 830 Progress Court, Oakville, Ontario L6L 6K1  
**Revision Date:** 01/24/2012  
**Product Use:** Diesel fuel detergent.  
**Chemical Family:** Petroleum distillates

**Section 2: Composition/Information on Ingredients**

Component Name:	%	LD50 and LC50	ACGIH TWA	Ecotoxicity - Aquatic Toxicity
Solvent Naphtha (Petroleum), Light Aromatic 64742-95-6	15-40	Inhalation LC50 Rat:3400 ppm 4h Oral LD50 Rat:8400 mg/kg Dermal LD50 Rabbit:2000 mg/kg Inhalation LC50 Rat:5.2 mg/L 4h	Not available	Not Available
1,2,4-Trimethylbenzene 95-63-6	10-30	Inhalation LC50 Rat:18 g/m <sup>3</sup> 4h Oral LD50 Rat:3400 mg/kg Oral LD50 Rat:8970 mg/kg Dermal LD50 Rabbit:3160 mg/kg	= 25 ppm TWA	LC50 (96 h) fathead minnow: 7.72 mg/L. Cond: flow-through LC50 (96 h) goldfish: 12.52 mg/L. Cond: flow-through LC50 (96 h) fathead minnow: 7.72 mg/L. Cond: flow-through
Stoddard Solvent 8052-41-3	7-13	Oral LD50 Rat: > 5000 mg/kg Dermal LD50 Rabbit: > 3000 mg/kg Inhalation LC50 Rat: > 1300 ppm 4h	= 100 ppm TWA	Not Available
Trimethylbenzene-1,3,5 108-67-8	3-7	Inhalation LC50 Rat:24 g/m <sup>3</sup> 4h Oral LD50 Rat:8970 mg/kg	= 25 ppm TWA	LC50 (96 h) goldfish: 12.5 mg/L. Cond: LC50 (96 h) goldfish: 12.52 mg/L. Cond: flow-through LC50 (72 h) goldfish: 13.7 mg/L. Cond: LC50 (96 h) fathead minnow: 7.72 mg/L. Cond: flow-through LC50 (96 h) fathead minnow: 3.48 mg/L. Cond: EC50 (24 h) water flea: 50 mg/L

## Section 2: Composition/Information on Ingredients

Xylene (mixture of isomers) 1330-20-7	1-5	Oral LD50 Rat:4300 mg/kg Inhalation LC50 Rat:5000 ppm 4h Dermal LD50 Rabbit:1700 mg/kg	= 100 ppm TWA =150 ppm STEL	LC50 (96 h) fathead minnow: 13.4 mg/L. Cond: flow-through LC50 (96 h) rainbow trout: 8.05 mg/L. Cond: flow-through LC50 (96 h) bluegill: 16.1 mg/L. Cond: flow-through EC50 (48 h) water flea: 3.82 mg/L EC50 (24 h) Photobacterium phosphoreum : 0.0084 mg/L
Solvent naphtha (Petroleum), Heavy aromatic 64742-94-5	1-5	Dermal LD50 Rabbit:2 mL/kg Inhalation LC50 Rat:590 mg/m <sup>3</sup> 4h Oral LD50 Rat:7050 mg/kg	Not available	Not Available
Cumene (Isopropylbenzene) 98-82-8	1-5	Oral LD50 Rat:1400 mg/kg Dermal LD50 Rabbit:3160 mg/kg	= 50 ppm TWA	LC50 (96 h) fathead minnow: 6.32 mg/L. Cond: flow-through EC50 (48 h) water flea: 0.6 mg/L EC50 (15 min) Photobacterium phosphoreum : 1.10 mg/L EC50 (30 min) Photobacterium phosphoreum : 1.48 mg/L EC50 (5 min) Photobacterium phosphoreum : 0.89 mg/L
Ethyl benzene 100-41-4	0.1-1.0	Dermal LD50 Rabbit:15354 mg/kg Inhalation LC50 Rat:17.2 mg/L 4h Oral LD50 Rat:3500 mg/kg	= 100 ppm TWA =125 ppm STEL	LC50 (96 h) bluegill: 150.0 mg/L. Cond: static LC50 (96 h) fathead minnow: 9.09 mg/L. Cond: flow-through LC50 (96 h) rainbow trout: 14.0 mg/L. Cond: static EC50 (48 h) water flea: 2.1 mg/L EC50 (30 min) Photobacterium phosphoreum : 9.68 mg/L
Naphthalene 91-20-3	0.1-1.0	Dermal LD50 Rat:2500 mg/kg Oral LD50 Rat:490 mg/kg Dermal LD50 Rabbit:20 g/kg Inhalation LC50 Rat:340 mg/m <sup>3</sup> 1h	= 10 ppm TWA =15 ppm STEL Skin - potential significant contribution to overall exposure by the cutaneous route	LC50 (96 h) fathead minnow: 6.14 mg/L. Cond: flow-through LC50 (96 h) rainbow trout (juvenile): 1.60 mg/L. Cond: flow-through LC50 (96 h) pink salmon (fry): 1.24 mg/L. Cond: static EC50 (48 h) water flea: 2.16 mg/L EC50 (30 min) Photobacterium phosphoreum : 0.93 mg/L

## Section 3: Hazards Identification

**Ingestion:**

Harmful if swallowed. Ingestion may cause respiratory irritation and central nervous system depression similar to inhalation. Ingestion of large amounts may cause stomach irritation. Symptoms include nausea, vomiting and diarrhea. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

**Inhalation:**

High concentrations may cause respiratory irritation and central nervous system depression with results ranging from dizziness and headache to unconsciousness.

### Section 3: Hazards Identification

**Skin Contact:** Moderate skin irritant.

**Eye Contact:** Severe eye irritant. May cause permanent eye damage. Vapours will irritate the eyes.

**Chronic Effects:** Reports have associated repeated and prolonged occupational overexposure to various organic solvents with internal organ, brain and nervous system damage. Prolonged or repeated exposure can result in drying of the skin, irritation and dermatitis. Contains materials which may cause cancer, depending on duration and level of exposure. See Section #11 for details.

### Section 4: First Aid Measures

**Ingestion:** Do not induce vomiting. Never give anything by mouth if victim is rapidly losing consciousness, is unconscious or is convulsing. Drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Obtain medical attention immediately.

**Inhalation:** If inhaled, remove to fresh air. If breathing is difficult give oxygen. If not breathing give artificial respiration and get medical attention immediately.

**Skin Contact:** Remove contaminated clothing and launder before reuse. Wash with soap and water. Seek medical attention if irritation persists.

**Eye Contact:** Get immediate medical attention. Immediately flush eyes with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses if any after the initial flushing and then continue flushing.

### Section 5: Fire Fighting Measures

**Flash Point (°C):** 43

**Flame Projection:** Not Applicable.

**NEPA Classification:** Combustible Liquid, Class II

**Lower Explosive Limit:** Not Available

**Upper Explosive Limit:** Not Available

**Autoignition Temp. (°C):** Not Available

**Sensitivity to Mechanical Impact:**

Not Available

**Conditions of Flammability:**

Flammable at all temperatures above the flash point on contact with an ignition source. Vapours are heavier than air and may travel or be moved along the ground to an ignition source at locations distant from material handling.

**Sensitivity to Static Discharge:**

Take precautionary measures against static discharges, such as bonding and grounding when dispensing.

**Hazardous Combustion:**

Carbon dioxide, carbon monoxide and other unidentified organic compounds.

**Extinguishing Media:**

Alcohol foam or water fog for large fires. Carbon dioxide or dry chemical for small fires. Use water spray to cool fire exposed containers and prevent bursting. Do not use a direct stream of water.

## Section 6: Accidental Release Measures

### Leak or Spill Procedures:

Wear suitable protective clothing. Follow applicable explosion and fire precautions during the response. Stop the spill at the source when safe to do so. For large spills, dike the area to prevent spreading. Pump excess to a salvage container. Absorb residues and small spills with a non-flammable absorbent material and collect adsorbate for disposal. For large quantities refer to the environmental ministry.

## Section 7: Handling and Storage

### Handling Procedures:

Containers of this material may contain hazardous residues when emptied. Do not cut, weld, drill or grind on or near this container. Use with adequate ventilation. Avoid breathing vapours or mist. Use good personal hygiene. Avoid smoking, eating and drinking during use. Wash with soap and water after handling.

### Storage Requirements:

Combustible liquid. Store in a cool, dry, well-ventilated area. Keep away from heat, sparks, ignition sources and oxidizing agents. Keep containers tightly closed when not in use. Keep away from children.

## Section 8: Exposure Controls / Personal Protection

<b>Respiratory:</b>	Not normally required. If the TLV is exceeded, a NIOSH-approved respirator is advised.
<b>Gloves:</b>	Neoprene. Nitrile gloves.
<b>Eyewear:</b>	Safety glasses. Contact lenses should not be worn. They may contribute to the severity of the injury.
<b>Clothing:</b>	Sufficient clothing to prevent skin contact.
<b>Ventilation:</b>	Sufficient mechanical ventilation to maintain exposures below the TLV. General mechanical ventilation is not recommended as the sole means of controlling exposure. Make-up air should always be supplied to balance air exhausted.
<b>Other protective equipment:</b>	Emergency showers and eyewash facilities should be nearby. The selection of personal protective equipment will vary depending on the conditions of use.

## Section 9: Physical and Chemical Properties

<b>Physical State:</b>	Liquid
<b>Color:</b>	Not Available
<b>Odour:</b>	Petroleum solvent
<b>Vapour Density (Air=1):</b>	> 1
<b>VOC %:</b>	Not Available
<b>pH:</b>	Not Applicable
<b>Solubility in Water:</b>	Negligible
<b>Specific Gravity (H<sub>2</sub>O=1):</b>	0.804
<b>Viscosity:</b>	< 14cSt @ 40°C

## Section 10: Stability and Reactivity

### Conditions of Instability:

Stable at ambient temperatures and pressures.

### Hazardous Polymerization:

Hazardous polymerization will not occur.

### Hazardous Decomposition:

See hazardous combustion products.

### Incompatible Materials:

Avoid strong oxidizers (e.g HOOH, HNO<sub>3</sub>).

**Conditions of Reactivity:**

Avoid contact with incompatible materials.

**Section 11: Toxicological Information****Irritancy of Product:**

Severe eye irritant. Moderate skin irritant. Respiratory irritant.

**Sensitization to product:**

Contains no known skin or respiratory sensitizers.

**Carcinogenicity:**

No components are listed as carcinogens by ACGIH, IARC, OSHA, or NTP. Contains 0.1 - 1.0% by wt naphthalene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by IARC. Contains 0.1 - 1.0% by wt ethylbenzene, which has been classified as a Group 2B carcinogen (possibly carcinogenic to humans) by IARC.

**Reproductive Effects:**

Not Available

**Teratogenicity:**

Contains a component that contains xylene. Xylene is reported to be fetotoxic.

**Mutagenicity:**

Not Available

**Synergistic Products:**

Not Available

**Section 12: Ecological Information****Environmental:**

This material contains substances that are expected to be harmful to aquatic organisms.

**Biodegradability:**

Not available.

**Section 13: Disposal Considerations****Waste Disposal:**

Reuse or recycling should be given priority over disposal under any circumstances. Do not dump unused contents into sewers, on the ground or into any body of water. Destroy by incineration or biological treatment according to applicable legislation. Dispose of in accordance with municipal, provincial and federal regulations.

**Section 14: Transportation Information****Road shipment:**

PETROLEUM PRODUCTS, N.O.S., Class 3, UN1268, PG III, ERG #128.

**Marine shipment:**

UN1268, PETROLEUM PRODUCTS, N.O.S., Class 3, PG III, EmS# F-E, S-E.

**Air Shipment:**

Petroleum Products, N.O.S., Class 3, UN1268, PG III, PI 309/310.

**Exemption:**

Not regulated for rail or road shipment based on Flammable Liquids General Exemption (i.e. no subsidiary class, flash point > 37.8 °C and contained in one or more small means of containment).

Product may be reclassified for air transportation if packaged in accordance to IATA regulations (i.e. Consumer Commodity, Class 9, ID 8000).

**Section 15: Regulatory Information**

WHMIS: B3 D2A D2B

CEPA: All components are listed on the Domestic Substances List (DSL).

## Section 15: Regulatory Information

**CPR Compliance:** This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

## Section 16: Other Information

**HMIS Rating:** 220B  
**Prepared By:** Regulatory Compliance, Shrader Canada Limited  
**Information Tel #:** 800-201-9486, 905-847-0222  
**Information Fax #:** 905-847-5404

CANUTEC EMERGENCY: 613-996-6666